

IN THE CLAIMS:

Please amend the claims as follows:

1. (currently amended) A motorized kitchen appliance, comprising:
a housing having a cylindrical outer wall with at least two recesses formed ~~therein in the outer wall~~, said recesses having openings in the outer wall; and
a drive unit having a motor disposed within the housing and projections matching a shape of said openings and projecting through said openings.
2. (original) The kitchen appliance according to claim 1, wherein said openings have a given height, and said projections are formed of resilient elements being slightly oversized as compared to said given height for being pressed into said openings.
3. (currently amended) The kitchen appliance according to claim 1, wherein the housing ~~which~~ further comprises a wall running in radial direction, said recesses having a cylindrical wall, and said openings occupying at least part of said cylindrical wall and part of said wall running in radial direction.
4. (currently amended) The kitchen appliance according to claim 1, wherein said drive unit has ~~a drive unit housing with~~ projecting lugs, and said projections are formed of resilient elements to be pressed onto said projecting lugs.
5. (original) The kitchen appliance according to claim 1, wherein said housing has an inner diameter, said cylindrical outer wall of said housing has an inner side with a strip having a height and running in axial direction at said inner side, for insertion of said drive unit into said housing along said strip, and said drive unit has a diameter smaller than said inner diameter of said housing minus said height of said strip.

6. (original) The kitchen appliance according to claim 2, wherein said openings have lead-in bevels in vicinity of said cylindrical wall of said recesses, for aiding said projections entering said openings.

7. (original) The kitchen appliance according to claim 1, which further comprises another outer wall bordering closely at and enclosing said cylindrical outer wall of said housing.

8. (currently amended) A motorized kitchen fruit press, comprising:
a housing having a cylindrical outer wall with at least two recesses formed ~~therein~~ in the outer wall, said recesses having openings in the outer wall;
a drive unit having a motor disposed within the housing and projections matching a shape of said openings and projecting through said openings; and
a rotating element driven by said drive unit for pressing fruit.